



Ø NB	A	Ø B	Ø C	D	L
25	68	115	16	125	100
40	88	150	18	140	115
50	102	165	20	160	125
65	122	185	20	180	145
80	138	200	22	200	155
100	158	220	24	250	175
125	188	250	26	250	200
150	212	225	26	320	225
200	268	340	30	390	275
250	320	405	32	390	325

SPECIFICATION OF STANDARDS	
DESIGN	DIN 3356 / F1
TESTS PRESSURE ( Kg / Cm <sup>2</sup> )	
	HYDROSTATIC
BODY	25
SEAT	16

10	HAND WHEEL	C.I. IS: 210 - Gr. FG 200
9	GLAND PLATE	C.I. IS: 210 - Gr. FG. 200
8	GLAND PACKING	ASBESTOSE ROPE GRAFITED
7	NUT & BOLT	CARBON STEEL
6	SPINDLE	S.S. ASI 410
5	GASKET	PURE GRAPHIT / CAF.
4	STOPPER	S.S. 410
3	BODY SEATRING	S.S. 410
2	BONNET	
1	BODY	C.I. IS: 210 - Gr. FG. 200
No.	DESCRIPTION	MATERIAL SPECIFICATION & GRAD

- NOTES :-
1. DIMENSIONS AND TEST PRESSURE ARE AS PER IS : 780 PN - 1
  2. FLANGE CAN BE DRILLED TO ANSI / BS / IS / STANDARDS AS REQUIRED
  3. ABOVE DIMENSIONS ARE SUBJECTED TO SPECIFIED TOLERANCE
  4. ALL DIMENSIONS ARE IN mm

SCALE : N.T.S. PROJ.

DRG. No. DV / ANGLE / D / 01 REV. No. 0

**MATERIAL & DESCRIPTIONS**

TITLE :-	DRN BY	L.B.G.
RIGHT ANGLE VALVE	CHECK BY	A.R.D.
	APPD BY	R. E. D.
	DATE	20.06.2008

**Dalsons Valves**  
D- 58, MIDC MIRAJ BLOCK MIRAJ  
DIST - SANGLI ( M.S. ) INDIA